

ELECTROMAGNETIC LOCKS

■ MAX. HOLDING FORCE: 500 KGS / 1100 LBS SERIES

- 500 mA @ 12VDC / 250 mA @ 24VDC
- Aluminum housing, weather resistant
- Monitored or unmonitored versions are available.
- Repels-residual magnetism.



EM-500/H SERIES

Model No.	EM-500/H	EM-500/HMR
Holding Force	Max. 500Kgs (1100 LBS)	Max. 500Kgs(1100 LBS)
Housing	Yes	Yes
Monitor	No	Yes
Reed Output	No	Yes
Size	266 x 66,5 x 41 mm	266 x 66,5 x 41 mm
Armature Size	185 x 60 x 12mm	185 x 60 x 12mm
Voltage	DC 12/24V	DC 12/24V

Model No.	EM-500/HNF/24	EM-500/HRNF/24	EM-500/HRNF/48
Holding Force	Max. 500Kgs (1100 LBS)	Max. 500Kgs (1100 LBS)	Max. 500Kgs (1100 LBS)
Housing	Yes	Yes	Yes
Monitor	No	No	No
Reed Output	No	Yes	Yes
Size	266 x 66,5 x 41mm	266 x 66,5 x 41mm	266 x 66,5 x 41mm
Armature Size	185 x 60 x 12mm	185 x 60 x 12mm	185 x 60 x 12mm
Fireproof	Yes	Yes	Yes
Voltage	DC 24V	DC 24V	DC 48V



EM-500/HNF SERIES

- Dual Voltage: 500 mA @ 12VDC / 250 mA @ 24VDC
- Aluminum housing, weather resistant
- Monitored or unmonitored versions are available.
- Repels-residual magnetism.



EM-D500 SERIES

Model No.	EM-D500H	EM-D500HMR
Holding Force	Max. 500Kgs x 2 (1100 LBS x 2)	Max. 500Kgs x 2 (1100 LBS x 2)
Housing	Yes	Yes
Monitor	No	Yes
Reed Output	No	Yes
Size	538 x 67 x 41mm	538 x 67 x 41mm
Armature Size	185 x 60 x 12mm	185 x 60 x 12mm